

Blacklight BL368 Compact

Lynx-S 11W BL 368

0025412



Range Features

- Features
- These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
-
- Directions for use
- Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m depending on the wattage



PRODUCT OVERVIEW

EAN code	5410288254128
Cap/Base	G23
Watt (Nominal) (W)	11
Ordering number	0025412
Voltage (V)	91

DATA TABLE

General data

EAN code	5410288254128
Cap/Base	G23
Ordering number	0025412

Blacklight BL368 Compact

Lynx-S 11W BL 368

0025412

Features

These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency
 100% improvement in effectiveness (at 368nm)
 Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
 Performs longer and better throughout the insect season

Range features

Directions for use

Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m depending on the wattage

Product name	Lynx-S 11W BL 368
Sales pack quantity	50
E-number FI	4940705

Electrical data

Watt (Nominal) (W)	11
Voltage (V)	91

Physical data

Single packaging type	Box/Sleeve
Weight (kg)	0.06
Outer package dimensions (L x W x H) (cm)	24.10 x 19.10 x 24.90
Single package dimensions (L x W x H) (cm)	2.30 x 3.60 x 23.70

TECHNICAL DRAWINGS

