


Lynx-D

Lynx D Basic 26w/830 G24d-3

0025797



Range Features

-



PRODUCT OVERVIEW

Lamp shape	Stick
Colour temperature (K)	3000
CRI (Ra)	82
Dimmable	No
EAN code	5410288257976
Energy class	A
Cap/Base	G24d-3
Type	Lynx D
Watt (Nominal) (W)	26
Light colour	830 White Delux
Ordering number	0025797
Efficacy (Rated) (lm/w)	66
Average life (Rated) (h)	10000
Luminous flux (Rated) (lm)	1780
Technology	Compact Fluorescent
Voltage (V)	105

DATA TABLE

Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
CRI (Ra)	82
Light colour	830 White Delux
Luminous flux (Nominal) (lm)	1780
Rated lumen maint. factor at 2000 h 50Hz	> 0.85
Rated lumen maint. factor at 4000 h 50Hz	> 0.78

Lynx-D

Lynx D Basic 26w/830 G24d-3

0025797

Rated lumen maint. factor at 6000 h 50Hz > 0.76

Rated lumen maint. factor at 8000 h 50Hz > 0.75

Luminous flux (Rated) (lm) 1780

General data

Average life (Nominal) (h) 10000

Control gear required Yes

Lamp shape Stick

Dimmable No

EAN code 5410288257976

Energy class A

General application Retail;Hospitality;Logistics and Industry;Museums;Education;Office;Residential & Consumer;

IEC Reference IEC 60901

IEC Reference 2 IEC 61199

Intended purpose General lighting

Cap/Base G24d-3

Lamp mercury content (mg) <2.5mg

Type Lynx D

Ordering number 0025797

Product name Lynx D Basic 26w/830 G24d-3

Average life (Rated) (h) 10000

Rated survival factor at 2000 h 50Hz > 0.98

Rated survival factor at 4000 h 50Hz > 0.95

Rated survival factor at 6000 h 50Hz > 0.85

Rated survival factor at 8000 h 50Hz > 0.50

Special purpose lamp No

Starting time (max) (s) <10s

Technology Compact Fluorescent

Transformer required Managtic ballast

Sales pack quantity 10

Warm-up time to 60% of full light (max) (s) 60

Electrical data

Current (A) 0.325

Ignition voltage (V) 198

kWh per 1000 hours burning time 31

Watt (Nominal) (W) 26

Efficacy (Rated) (lm/w) 66

Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp. 66

Lynx-D

Lynx D Basic 26w/830 G24d-3

0025797


Watt (Rated) (W)	26
Voltage (V)	105

Physical data

Max. Lamp Diameter (mm) - D	22
Lamp Length (mm) - C/L	170
Length base to base (mm) - A	15.6
Single packaging type	Box/Sleeve
Weight (kg)	0.08
Outer package dimensions (L x W x H) (cm)	36.50 x 19.50 x 4.50
Single package dimensions (L x W x H) (cm)	18.50 x 3.50 x 3.50

TECHNICAL DRAWINGS

G24d



Lynx-D

Lynx D Basic 26w/830 G24d-3

0025797

