



MODEL	P	W	F	T	H	A
EOL 100	+	+	-	-	-	-
EOL 100 BT	-	-	-	-	-	-
EOL 100 T	-	-	-	+	-	-
EOL 100 FT	-	-	+	+	-	-
EOL 100 HT	-	-	-	+	+	-
EOL 1012	-	-	-	-	-	-
EOL 120	+	+	-	-	-	-
EOL 120 B	-	-	-	-	-	-
EOL 120 T	-	-	-	+	-	-
EOL 120 FT	-	-	+	+	-	-
EOL 120 HT	-	-	-	+	+	-
EOL 150	+	+	-	-	-	-
EOL 150 B	-	-	-	-	-	-
EOL 150 T	-	-	-	+	-	-
EOL 150 FT	-	-	+	+	-	-
EOL 150 HT	-	-	-	+	+	-

P - pull cord switch, W - cable with a plug,
F - photocell, T - time switch,
H - adjustable humidity sensor, A - automatic louver

Type	Size [mm]					Weight [kg]	V	Hz	W	Reinforcement	Air flow [m³/h]	Class	Protection	Acoustical pressure	rev. [1/min]
	A	B	C	D	E										
EOL 100	130	140	100	100	10	0,54	230	50	19	flux	100	II	IP - X4	39 dB (A)	2550
EOL 120	150	162	100	120	10	0,61	230	50	20	flux	150	II	IP - X4	42 dB (A)	2360
EOL 150 (LS)	170	180	100	150	10	0,70	230	50	22	flux	200	II	IP - X4	45 dB (A)	1850
EOL 150 (HS)	170	180	100	150	10	0,75	230	50	24	flux	300	II	IP - X4	47 dB (A)	2350
EOL 1012	130	140	100	100	10	0,53	12	50	19	flux	100	II	IP - X4	39 dB (A)	2550

