

Blacklight BL368 Linear & Circline

F6W/T5/BL368

0000088



Range Features

- BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes
- Applications
- Insect traps, insect attraction is strongly increased
- Restaurants, kitchens, food shops, supermarkets
- Diazo printing machines
- Photo Polymerisation
- Chemical processing
- Mineral detection
- Various technical applications
- Directions for use
- Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage



PRODUCT OVERVIEW

Lamp finish	Coated
Dimmable	Yes
EAN code	5410288000886
Type	T5-Special
Watt (Nominal) (W)	6
Ordering number	0000088

DATA TABLE

General data

Control gear required	Yes
Lamp finish	Coated
Dimmable	Yes
EAN code	5410288000886
Type	T5-Special
Ordering number	0000088

Blacklight BL368 Linear & Circline

F6W/T5/BL368

0000088

Range features	<p>BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency</p> <p>100% improvement in effectiveness (at 368nm)</p> <p>Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)</p> <p>Performs longer and better throughout the insect season</p> <p>Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes</p> <p>Applications</p> <p>Insect traps, insect attraction is strongly increased</p> <p>Restaurants, kitchens, food shops, supermarkets</p> <p>Diazo printing machines</p> <p>Photo Polymerisation</p> <p>Chemical processing</p> <p>Mineral detection</p> <p>Various technical applications</p> <p>Directions for use</p> <p>Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage</p>
-----------------------	--

Product name	F6W/T5/BL368
Sales pack quantity	25
E-number FI	4940421

Physical data

Max. Lamp Diameter (mm) - D	16
Lamp Length (mm) - C/L	226.3
Length base to base (mm) - A	212.1
Length base to pin Min-Max - B	216.8-219.2
Single packaging type	Box/Sleeve
Weight (kg)	0.02
Outer package dimensions (L x W x H) (cm)	24.00 x 11.00 x 10.50
Single package dimensions (L x W x H) (cm)	22.60 x 1.90 x 1.90

Electrical data

Watt (Nominal) (W)	6
---------------------------	---

TECHNICAL DRAWINGS

Blacklight BL368 Linear & Circline

F6W/T5/BL368

0000088

